







产品简介
PRODUCT INTRODUCTION




JQX-15F/T90 Electromagnetic relay series

产品图示	技术参数	安装尺寸图
PRODUCT ILLUSTRATION	TECHNICAL PARAMETER	TECHNICAL PARAMETER
	Dimension: 32.4x27.5x19.5 Electric contact: 1C.1H.1D Electric load: 30A, 40A Switching Voltage: 277VAC/30VDC contact: Silver alloy Coil power: DC 0.93W AC 1.2VA Coil voltage: DC 3V~110V, AC 6V~240V Electrical life: $\geq 10^5$ Installation: PCB printing plate Certification: 	


JQX-15F/T91 Electromagnetic relay series

产品图示	技术参数	安装尺寸图
PRODUCT ILLUSTRATION	TECHNICAL PARAMETER	TECHNICAL PARAMETER
	Dimension: 32.4x27.4x28.6 Electric contact: 1C.1H.1D Electric load: 30A, 40A Switching Voltage: 277VAC/30VDC contact: Silver alloy Coil power: DC 0.93W AC 1.2VA Coil voltage: DC 3V~110V, AC 6V~240V Electrical life: $\geq 10^5$ Installation: PCB printing plate Certification: 	

JQX-15F/T93 Electromagnetic relay series


产品图示	技术参数	安装尺寸图
PRODUCT ILLUSTRATION	TECHNICAL PARAMETER	TECHNICAL PARAMETER
	Dimension: 32.4x27.4x21 Electric contact: 1C.1H.1D Electric load: 30A, 40A Switching Voltage: 277VAC/30VDC contact: Silver alloy Coil power: DC 0.93W AC 1.2VA Coil voltage: DC 3V~110V, AC 6V~240V Electrical life: $\geq 10^5$ Installation: PCB printing plate Certification: 	

PYF11A Base series


产品图示	技术参数
PRODUCT ILLUSTRATION	TECHNICAL PARAMETER
	Load current: 7A Load voltage: 300V Medium pressure: 2500VAC/S Applicable relay: JQX-18F-3Z, HH53P, MY3

产品简介
PRODUCT INTRODUCTION


PYF08A1、PYF08A-E1、PYF08A2 Base series

产品图示	技术参数
PRODUCT ILLUSTRATION	TECHNICAL PARAMETER
	Load current: 7A Load voltage: 300V Medium pressure: 2500VAC/S Applicable: JQX-18F-2Z, HH52P, MY2 relay

PYF14A1、PYF14A-E1 Base series

产品图示	技术参数
PRODUCT ILLUSTRATION	TECHNICAL PARAMETER
	Load current: 7A Load voltage: 300V Medium pressure: 2500VAC/S Applicable: JQX-18F-4Z, HH54P, MY4 relay

PTF08A Base series

产品图示	技术参数
PRODUCT ILLUSTRATION	TECHNICAL PARAMETER
	Load current: 12A Load voltage: 300V Medium pressure: 2500VAC/S Applicable: JQX-13F-1Z, JQX-13F-2Z, HH61P, HH62P, LY1, LY2 relay

※由于标准和材料的变更，文中所述特征和本资料中的图像仅供参考，一切以实物为准，我公司保留最终解释权。

产品简介
PRODUCT INTRODUCTION
致力于未来
FOCUS ON THE FUTURE






公司简介
COMPANY PROFILE

浙江格亚电气有限公司是一家引进国内外先进的生产设备和专业技术，专业从事继电器的研发、生产、销售、服务为一体的综合性企业。座落于中国电器之都——柳市。为能在日益激烈的全球化市场竞争中实现公司的可持续发展，格亚电器将继续秉承“诚信、超越”的经营理念，以高性价比的产品、快速的交货期和优质的售后服务来满足全球客户的需求。






产品简介
PRODUCT INTRODUCTION

JQX-13F/2Z Electromagnetic relay series




产品图示	技术参数	安装尺寸图
PRODUCT ILLUSTRATION	TECHNICAL PARAMETER	TECHNICAL PARAMETER
	Dimension: 27.3x21x35 Electric contact: 2C.2H.2D Electric load: 12A Switching Voltage: 240VAC/28VDC contact: Silver alloy Coil power: DC 0.9W AC 1.2VA Coil voltage: DC 6V~220V, AC 6V~380V Electrical life: $\geq 10^5$ Installation: PCB printing plate, base Certification: 	

产品简介
PRODUCT INTRODUCTION




HH52P Electromagnetic relay series

产品图示	技术参数	安装尺寸图
PRODUCT ILLUSTRATION	TECHNICAL PARAMETER	TECHNICAL PARAMETER
	Dimension: 27.3x21x35 Electric contact: 2C.2H.2D Electric load: 6.5A Switching Voltage: 240VAC/28VDC contact: Silver alloy Coil power: DC 0.9W AC 1.2VA Coil voltage: DC 3V~220V, AC 3V~380V Electrical life: $\geq 10^5$ Installation: PCB printing plate, base Certification: 	




HH53P Electromagnetic relay series

产品图示	技术参数	安装尺寸图
PRODUCT ILLUSTRATION	TECHNICAL PARAMETER	TECHNICAL PARAMETER
	Dimension: 27.3x21x35 Electric contact: 3C.3H.3D Electric load: 6.5A Switching Voltage: 240VAC/28VDC contact: Silver alloy Coil power: DC 0.9W AC 1.2VA Coil voltage: DC 3V~220V, AC 3V~380V Electrical life: $\geq 10^5$ Installation: PCB printing plate, base Certification: 	

HH54P Electromagnetic relay series




产品图示	技术参数	安装尺寸图
PRODUCT ILLUSTRATION	TECHNICAL PARAMETER	TECHNICAL PARAMETER
	Dimension: 27.3x21x35 Electric contact: 4C.4H.4D Electric load: 5A Switching Voltage: 240VAC/28VDC contact: Silver alloy Coil power: DC 0.9W AC 1.2VA Coil voltage: DC 3V~220V, AC 3V~380V Electrical life: $\geq 10^5$ Installation: PCB printing plate, base Certification: 	

JQX-13F/3Z Electromagnetic relay series




产品图示	技术参数	安装尺寸图
PRODUCT ILLUSTRATION	TECHNICAL PARAMETER	TECHNICAL PARAMETER
	Dimension: 27.3x31x35 Electric contact: 3C.3H.3D Electric load: 12A Switching Voltage: 240VAC/28VDC contact: Silver alloy Coil power: DC 1.5W AC 2.5VA Coil voltage: DC 6V~220V, AC 6V~380V Electrical life: $\geq 10^5$ Installation: PCB printing plate, base Certification: 	

产品简介
PRODUCT INTRODUCTION




JQX-38F Electromagnetic relay series

产品图示	技术参数	安装尺寸图
PRODUCT ILLUSTRATION	TECHNICAL PARAMETER	TECHNICAL PARAMETER
	Dimension: 55.5x30x37.5 Electric contact: 2C.2H.2D.3C.3H.3D Electric load: 40A, 50A Switching Voltage: 240VAC/28VDC contact: Silver alloy Coil power: DC 2.5W AC 6VA Coil voltage: DC 6V~220V, AC 6V~380V Electrical life: $\geq 10^5$ Installation: Base Bolt type Certification: 	


JQX-40F Electromagnetic relay series

产品图示	技术参数	安装尺寸图
PRODUCT ILLUSTRATION	TECHNICAL PARAMETER	TECHNICAL PARAMETER
	Dimension: 60x46x46 Electric contact: 1C.1H.1D Electric load: 40A Switching Voltage: 240VAC/28VDC contact: Silver alloy Coil power: DC 2.0W AC 8.6VA Coil voltage: DC 6V~220V, AC 6V~380V Electrical life: $\geq 10^5$ Installation: Bolt type Certification: 	

JQX-60F Electromagnetic relay series

产品图示	技术参数	安装尺寸图
PRODUCT ILLUSTRATION	TECHNICAL PARAMETER	TECHNICAL PARAMETER
	Dimension: 60x46x46 Electric contact: 1C.1H.1D Electric load: 50A, 60A Switching Voltage: 240VAC/28VDC contact: Silver alloy Coil power: DC 2.0W AC 8.6VA Coil voltage: DC 6V~220V, AC 6V~380V Electrical life: $\geq 10^5$ Installation: Bolt type Certification: 	

JQX-13F/4Z 电磁继电器系列

产品图示	技术参数	安装尺寸图
PRODUCT ILLUSTRATION	TECHNICAL PARAMETER	TECHNICAL PARAMETER
	Dimension: 27.3x41x35 Electric contact: 4C.4H.4D Electric load: 12A Switching Voltage: 240VAC/28VDC contact: Silver alloy Coil power: DC 1.5W AC 3VA Coil voltage: DC 6V~220V, AC 6V~380V Electrical life: $\geq 10^5$ Installation: PCB printing plate, base Certification: 