




SEARCH RESULT
SPEC | REPORT

CERTIFICATE

| OTHERS

 Share





(for DA Type only)



(for ELG 100 C1050,C1400 only)



SELV (for ELG 100 C1050,1400 only)

IP65 IP67



■ Features

- Constant Current mode output
- Metal housing design with functional Ground
- Built-in active PFC function
- No load / Standby power consumption <0.5W
- IP67 / IP65 rating for indoor or outdoor installations
- Function options: output adjustable via potentiometer; 3 in 1 dimming (dim-to-off); Smart timer dimming; DALI
- Typical lifetime >50000 hours
- 5 years warranty

■ Applic

- LED stre
- LED har
- LED bay
- LED gre
- LED floo
- Type "H hazardous

■ Description

ELG-100-C series is a 100W LED AC/DC driver featuring the constant current high voltage output. ELG-100-C operates from 100~360VAC and offers mod rated current ranging between 350mA and 1400mA. Thanks to the high effic with the fanless design, the entire series is able to operate for -40°C~+90°C ca free air convection. The design of metal housing and IP67/IP65 ingress prote this series to fit both indoor and outdoor applications. ELG-100-C is equippe options, such as dimming methodologies, so as to provide the optimal desig lighting system.

■ Model Encoding